

CEMS Application Completion Check

South Coast Air Quality Management District • Source Test Engineering Branch



Before you submit your CEMS Application, did you: Identify the type of CEMS to be installed (RECLAIM, non-RECLAIM, single-dedicated CEMS, time-shared CEMS, ACEMS, FSMS)? Identify whether this is a new CEMS, or an existing CEMS modification? Fully identify the source(s) monitored by the CEMS and pollutants to be monitored, permitted pollutants limits, the AQMD identification (Permit-to-Construct, Permit-to-Operate, Facility ID), and attach a copy of the Permit? Describe the process(es) monitored, expected contaminant gas concentrations and attach a drawing of the process? Describe the exhaust stack where the CEMS will acquire a gas sample and attach a drawing? Describe the components of the CEMS (analyzers, flow measurements, DAS, PLC, recorders), and attach a schematic drawing and vendors specification sheets? Identify how pollutant emissions will be calculated, recorded, and reported, and the programming logic involved to meet compliance with all applicable AQMD rules and permit conditions concerning CEMS monitoring? Supplemental sheets concerning other facility sources which will use this CEMS information? (RECLAIM ONLY): Have you contacted Mr. George Haddad (ghaddad@aqmd.gov) concerning your RTU reporting obligations? CEMS Quality Assurance Plan (QAP) to be submitted before CEMS Certification can be issued? Facility contact information, and signed and dated by a facility representative (not a consultant or a source test lab)? The completed CEMS Application includes: \square Completed PART 4 of this packet, plus appropriate basic processing fee, \quad \text{and a cover letter briefly describing your CEMS situation.} DO NOT attach this CEMS Application, Form ST-400, or CEMS fees to any other AQMD correspondence (Permitting submittals, etc.). CEMS Application and Certification is handled separately from the Permitting process. This submittal must be directed to: SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT Monitoring & Analysis Division, Source Test Engineering Branch 21865 Copley Drive Diamond Bar, CA 91765-4182* *expedited FedEx, UPS, USPS or courier delivery: mark envelope "Hold at Front Desk for

Pick-up by Source Testing Staff (ext. 3479)"



South Coast Air Quality Management District 21865 E. Copley Drive, Diamond Bar, CA 91765-4182

FORM ST-220AP

Monitoring & Analysis Division, Source Test Engineering Branch (909) 396-3479

APPLICATION FOR INITIAL CERTIFICATION, OR MODIFICATION, OF RECLAIM AND NON-RECLAIM CONTINUOUS EMISSIONS MONITORING SYSTEMS (CEMS)

	Applicant: Please che	ck al	ll that are a	oplicable re	egardin	g your si	ıbmittal:		
Present Status:	Currently or Proceedings of Certification no.			ified)	1 S] New Source		RECLAIM Non-RECLAIM	
Type Application:			ication / F				☐ Rule/	Permit Change	
Source(s) Monitored:			than one (than one <u>S</u>			,	y):	(specify number)	
Type(s) of CEMS:	□ NOx □ CO □ SOx □ Fuel		O ₂ Flow	Tim Shared	-		MS EMS	ACEMS	
	requested information below. If additional space is requi								Γest
1. APPLICAN	T, COMPANY, CON	TAC	CT INFO	RMATIC	ON				
Facility II) No	:							_
Facility Pe	ermit Holder	:							_
Mailing A	ddress	:							- -
Equipmen	t Location								=
(Also include	Company Name if different s License Name listed above)	•							- -
Company	Contacts	:			Name			rnone	
		•			1 itie			E-maii Address	
		:			name			rnone	
					Lifle			H-mail Address	

¹ Be sure to attach a copy of your most recent CEMS Certification to this Application.

- **2. CEMS HISTORY AND REPORTING REQUIREMENTS** Please provide some background concerning your CEMS proposal so that we can better determine if you are fulfilling (or overfulfilling) your CEMS monitoring obligations
 - a. SOURCE (OR SOURCES) MONITORED BY THIS CEMS

SOx CEMS Applicants Only: If this CEMS is an FSMS, also complete Appendix F.

EQUIPMENT 1:				
AQMD .	Appl	ication/Permit No. or REC	LAIM Device I.D.	
Description (from Application or Permit, including control equipment)	:			
Operating Rate (incl units)	:	Design	Normal	Minimum
Process Characteristic	:	☐ Continuous ☐ Intermittent ² :		(hrs/batch)(hrs/day) or (/)
EQUIPMENT 2:				
AQMD Description (from Application or Permit, including control equipment)	Appl	ication/Permit No. or REC	LAIM Device I.D.	
Operating Rate (incl units)	:	Design	Normal	Minimum
Process Characteristic	:	☐ Continuous ☐ Intermittent²		(hrs/batch)(hrs/day) or (/)
EQUIPMENT 3:				
AQMD Description (from Application or Permit, including control equipment)	Appl :	ication/Permit No. or REC	LAIM Device I.D.	
Operating Rate (incl units)	:	Design	Normal	Minimum
Process Characteristic	:	☐ Continuous ☐ Intermittent ² :		(hrs/batch)(hrs/day) or (/)

 $^{^2}$ Equipment operates on-demand, is supplemental, or is a back-up to another piece of equipment.

		nstall date:)
CEMS instal	led CEMS installed & Oper	ating (date:)
Briefly describe self-elected) and Construct, or Per your continuous assure that you	what necessitated this CEMS I attach a copy of the applicable rmit-to-Operate in <i>Attachment 1</i> monitoring requirements with have fulfilled all of your monitoring	e part of the AQMD Facility (It is recommended that you your assigned AQMD Pern oring obligations, and also to	Permit, Permit-to- thoroughly discuss nitting Engineer to assure that you are
Contaminant <u>Monitored</u>	Applicable Rule or Permit Condition or "Self Elected"	Continuous Monitoring	g Requirement
NOx		Concentration Limit: (corrected Mass Emission (unit):	d to: $\square 3\% \square 15\% O_2$)
SOx		Concentration Limit:(corrected	ppm d to: 3% 15% O2)
СО		Concentration Limit:	d to: 3% 15% O ₂)
other:		Concentration Limit:(corrected	d to: $\square 3\% \square 15\% O_2$)
Comments conce	erning above requirements:		
AQMD CONTA	ACTS		
Permitting Engir	neer:		
Inspector:			(phone ext)
Source Testing I	Engineer:		(phone ext)
	CEMS not in CEMS instal CEMS REPOR Briefly describe self-elected) and Construct, or Peryour continuous assure that you inot proposing to Contaminant Monitored NOx SOX CO other: Comments concerning Engineering Engine	CEMS REPORTING REQUIREMENTS Briefly describe what necessitated this CEMS self-elected) and attach a copy of the applicabl Construct, or Permit-to-Operate in Attachment I your continuous monitoring requirements with assure that you have fulfilled all of your monitonot proposing to monitor a contaminant Monitored Condition or "Self Elected" NOx SOX COMMENT COMMEN	CEMS not installed (approx: order install date: CEMS installed CEMS installed & Operating (date: CEMS REPORTING REQUIREMENTS Briefly describe what necessitated this CEMS proposal (District Rules, Perself-elected) and attach a copy of the applicable part of the AQMD Facility Construct, or Permit-to-Operate in Attachment 1. (It is recommended that you your continuous monitoring requirements with your assigned AQMD Pern assure that you have fulfilled all of your monitoring obligations, and also to not proposing to monitor a contaminant³ that is not required to be continuously. Contaminant Monitored Mass Emission (unit): NOx Concentration Limit: (corrected Mass Emission (unit): SOx Concentration Limit: (corrected Mass Emission (unit): Concentration Limit: (corrected Mass Emission (unit): Comments concerning above requirements: AQMD CONTACTS Permitting Engineer: (name) Inspector: (name)

³ There is a distinction between contaminants which require continuous monitoring (CEMS), and contaminants which are required to be monitored periodically or non-continuously, such as annual CO and NOx monitoring for Permit Compliance. These distinctions aren't always clearly explained in the Permit Conditions. Be sure to contact an AQMD Permitting Engineer for clarification on what is - and what is not required before proceeding with a CEMS Application.

3. PROCESS DESCRIPTION

Briefly describe manufacturing and control processes in the space below, and include a simplified process flow diagram in Appendix A.

4. FUEL AND FLUE GAS INFORMATION

Please include a simplified stack diagram in Appendix B. <u>ACEMS Applicants</u>: Complete specified sections only. <u>Time-Shared CEMS Applicants</u>: Make copies of this page and list information based on individual sampling locations.

a. STACK SAMP (ACEMS Applicants: 1				Diam	eter or Le	ength	Wid	lth
Stack dimensions			:	: 				
Overall stack heigh	t		:			in _.	ft.	in.
CEMS probe tip dis	stance in stack fr	om stack wall			ft.		in.	
(ACEMS Applicants: does n		0111 0 000 011			ft.		in.	
CEMS probe distant (ACEMS Applicants: this is					ft.		in.	
CEMS probe distant (ACEMS Applicants: this is	•		: e)		ft.		in.	
Reference sample p		n CEMS probe	e :		ft.	in.		tream vnstream check)
b. ANTICIPATEI	FLUE OR ST	ACK PARAN	METERS					
Contaminant Gas	: NO _x :	to	ppm	SO_x	:	to_		ppm
	CO :	to	ppm	():	to_		ppm
(Other gas)	():	to	ppm	():	to_		ppm
Diluent Gas	: CO ₂ :	to	%	O_2	:	to_		%
(Other gas)	():	to	%	():	to_		
Temperature:	to	°F	Static Pre	es:		to		" H ₂ O
Moisture:	to		Flowrate	: <u> </u>		to		dscfm
Particulate Matter	:		to					gr/dscf
c. ANTICIPATEI) FUEL PARAN	METERS						
Fuel Type	: Natural G	as (specify)						
Sulfur Content ⁴	:		to					ppm
CO ₂ ⁴ :	to		Usage Ra	ite:		to		dscfm
Moisture ⁴ :	<u>to</u>		Meter Pro	es:		to		psig

⁴ Only applies for fuel other than natural gas.

	IPLE	GAS ANAL			Mala Lena	D 1		
Gas Monitored		Make	Model		Method of Detection (NDIR, etc.)	Proposed Range(s)	(chec	
PRINC	IPLE	FLOW MO	NITOR					
Type:		Make	Model	Princip	ple (Orifice, Pitot, etc.)	Proposed Range	(check	
fuel flow				Des	scription or Purpose		cor u	
SUPPL	EME	NTAL COM	PONENTS ⁷ / P	RINCI	PLE ACEMS COM	PONENTS		
Paramete	Parameter Make		Model	Description or Purpose				
SAMPI	LE AC	CQUISITION	& CONDITIO	ONING	SYSTEM (probe, child	ler, etc.)		
SAMPI Make	LE AC	CQUISITION Model	& CONDITIO	ONING	SYSTEM (probe, child Description	ler, etc.)		
	LE AC		I & CONDITIO (□ Single-P		W	,		
	LE AC			oint 🗌	Description Multiple ⁸ -Point Probe)	,		
	LE AC		(Single-P	oint 🗌	Description Multiple ⁸ -Point Probe)	,		
Make DATA	ACQ	Model WISITION &	(Single-P (Conditioning	oint g Systen G EQUI	Description Multiple ⁸ -Point Probe) 1 / Chiller): PMENT (Computer, D	:	order etc	
Make DATA	ACQ	Model WISITION &	(Single-P	oint g Systen G EQUI	Description Multiple ⁸ -Point Probe) 1 / Chiller): PMENT (Computer, D	:	order etc	
Make DATA non-REC	ACQ	Model WISITION & only: indicate w.	(Single-P (Conditioning) REPORTING	oint g Systen G EQUI	Description Multiple ⁸ -Point Probe) 1 / Chiller): PMENT (Computer, Eal record).	:	order etc	
Make DATA non-REC	ACQ	Model WISITION & only: indicate w.	(Conditioning) REPORTING which component will (DAS):	oint g Systen G EQUI	Description Multiple ⁸ -Point Probe) 1 / Chiller): PMENT (Computer, Eal record).	:	order etc	
Make DATA non-REC	ACQ	Model WISITION & only: indicate w.	(Single-P (Conditioning) REPORTING	oint g Systen G EQUI	Description Multiple ⁸ -Point Probe) 1 / Chiller): PMENT (Computer, Eal record).	:	order etc	

⁵ Specify whether reported raw gas reading will be to "dry" or "wet" conditions, excluding external corrections (If any readings are "wet", be

Specify whether reported raw gas reading will be to "dry" or "wet" conditions, excluding external corrections (If any readings are "wet", be sure to detail how they will be corrected to dry standard conditions in *Appendix D*).

Specify whether reported raw fuel or flue reading will be corrected "unc" or uncorrected "cor" to dry standard conditions, excluding external corrections (If readings will be "unc", be sure to detail how they will be corrected to dry standard conditions in *Appendix D*).

Components used to augment the performance of the principle gas and flow components listed in a. & b. (temperature, pressure, and moisture correction devices, for instance).

Be sure to complete *Appendix C1*. You must successfully bench-test this probe before CEMS Initial Approval can be granted.

6.	CEMS EXPENDIT	JRE		T . 10
	Estimated Cost of I	Equipment : \$	Equipment & Materials	Total System as Installed \$
	CEMS Contractor	:		
	Address	:		
	Phone	:		
	Check below how requirements for each these parameters with assumptions, and call conditions, or conditions are commonly a explanation and supparticular monitoring	you propose to a monitored pollu Il be applied to culations. (Be s ons imposed by ccepted equation porting document situation:	b MONITORING PARAME of meet applicable rule and attent of this CEMS. Detail, steed the final monitoring requireure to detail how corrections rules or permits.). Constants, fins; or non-standard equations, tation (historical data, etc.).	permit condition monitoring up by step in <i>Appendix D</i> , how rement by use of equations, will be made to dry, standard factors, and/or coefficients not must be submitted with full Check all that apply for your
Gas	Concentration	Based On:	Flowrate Based On:	Emission Rate Based On:
NOx	Predicted (AC		☐ Direct Stack Flow Meas. ☐ Predicted ACEMS/PEMS ☐ Standard Fuel F-Factor ☐	Direct (conc x stack flow) Predicted (ACEMS/PEMS) Standard Fuel F-Factor
SOx	Predicted (AC Fuel Sulfur Co	EMS/PEMS)	☐ Direct Measurement ☐ Predicted ACEMS/PEMS ☐ Fuel Usage ☐ Standard Fuel F-Factor ☐	Direct (conc x flowrate) Predicted (ACEMS/PEMS) Fuel Sulfur Content (FSMS) Fuel F-Factor
CO:	Predicted (AC		☐ Direct Stack Flow Meas. ☐ Predicted ACEMS/PEMS ☐ Standard Fuel F-Factor	Direct (conc x stack flow) Predicted (ACEMS/PEMS) Standard Fuel F-Factor
:	☐ Direct Gas Me☐ Predicted (AC☐ + O₂ Correction		☐ Direct Stack Flow Meas. ☐ Predicted ACEMS/PEMS ☐ Standard Fuel F-Factor	Direct (conc x stack flow) Predicted (ACEMS/PEMS) Standard Fuel F-Factor

8. COMPUTER PROGRAMMING LOGIC FOR THE PARAMETERS IN SEC. 7

Briefly describe in *Appendix E* how these parameters will be programmed into the data reduction and recording units. Use block diagrams, or a copy of recorded data if needed, to show the location in the program where constants, variables and other parameters are entered. Indicate DAS polling frequency. *ACEMS Applicants* must also discuss redundancy and/or remediation for primary parameter error or failure.

9. APPLICABLE PERMITS AND PERMIT CONDITIONS

Please attach applicable permits and permit conditions related to all basic and control equipment which will be monitored by the CEMS (Label as "Attachment 1", or attach to sheet provided).

10. MANUFACTURER'S OR VENDOR'S CEMS SPECIFICATIONS

Please attach manufacturer's or vendor's specification sheets for all equipment or devices which relate to the CEMS (Label as "Attachment 2", or attach to sheet provided).

11. OA/OC PROCEDURES

All CEMS applicants⁹ shall submit a <u>complete</u> Quality Assurance Plan (QAP) according to RECLAIM Regulation XX and Rule 218. In this Plan, you must address the on-going maintenance and contingencies necessary to assure the continued reliability of emission information. Discuss scheduled and unscheduled maintenance, contingencies for equipment/CEMS outages and modifications, recordkeeping and reporting, periodic testing, personnel responsible for assuring implementation of this Plan, etc. If you have already prepared a QAP for this CEMS, please include a copy with this Application, and label it as "Attachment 3". If the QAP is not yet completed, briefly describe or outline its content, and include it as "Attachment 3". NOTE TO ALL APPLICANTS: The completed QAP must be submitted, and approved before CEMS "Final Certification can be granted.

12. REMOTE TERMINAL UNIT (RTU) (RECLAIM CEMS Applicants Only)

Although not technically classified as a part of the CEMS which you have described in this Application, an approved RTU is required, pursuant to District RECLAIM RULES 2011 and 2012, to electronically report CEMS emission information to the District on a daily basis (or at an interval specified by other rules or permit conditions). Please contact Mr. George Haddad in the District's Information Management Division (IM), at (909) 396-2650 (e-mail: ghaddad@aqmd.gov) for more information regarding RTU specifications, capabilities, and approval. For our records, please indicate present RTU status:

approval. For our records, please indicate present RTU status:
This proposed CEMS will use an existing RTU which is capable of connecting to the District (serves previously certified CEMS or CEMS undergoing certification, at this facility).
There is presently no RTU installed at this facility. Part of this CEMS proposal includes RTU specifications which will be forwarded to the person listed above.
New RTU is installed and is capable of connecting to the AQMD.

⁹ Effective May 14, 1999, Non-RECLAIM CEMS applicants must also prepare a QAP. ACEMS applicants shall submit a QAP for each parameter measured.

13.	CEMS INSTRUMENT ENCLOSURE (Please indicate below):
	☐ CEMS will be enclosed in an environmentally-controlled shelter with: ☐ Temperature alarm or record of exceedances of manufacturer's specified operating range. ☐ No provisions for temperature alarm or record (Additional QA certification testing required).
	CEMS shelter will <u>not</u> be environmentally-controlled (Additional QA certification testing shall be required).
14.	NON-RECLAIM CEMS CERTIFICATION OPTIONS (Non-RECLAIM CEMS Applicants
	Only Non-RECLAIM or "Command-and-Control CEMS Applicants must indicate before Final CEMS Certification, by checking the appropriate box below, how they will certify, and maintain this CEMS (be sure to read both of these documents before deciding):
	CEMS is to be reviewed and certified according to the performance specifications of Rule 218.1, and will be subject to Rule 218.1 Quality Assurance requirements.
	☐ CEMS is to be reviewed and certified according to the applicable performance specifications of 40CFR60, Appendix B, and will be subject to the Quality Assurance requirements of 40CFR60, Appendix F.
15.	MULTI-POINT PROBE REQUIREMENTS (Multi-Point Probe Applicants Only) I have read and understand the procedures for "pre-certifying" the multiple-point probe for my CEMS, and the continued QA measures as described in AQMD Source Testing Form 511: "Multi-Point Probe Acceptance and Quality Assurance Standards, for Use in Conjunction with EPA/EMTIC Guidance Document (GD)-031". I understand that the completed probe benchtest report must be submitted to the AQMD for formal approval before the probe may be installed in the stack sampling location, and that issuance of CEMS Initial Approval will be contingent upon the successful completion of this task.
16.	EXPEDITED REVIEW REQUESTED (Read Below, Carefully, Before Requesting) I have read District Rule 301(y)(3) regarding the provisions for an expedited CEMS certification review, and I understand that it entails paying additional fees upon completion of this project, and that the decision to grant expedited review will be at the discretion of the Manager of the Source Testing Branch of the AQMD. I also understand the limitations concerning CEMS expedited review: The only processes involving CEMS Certification which can be expedited concern AQMD's responsibility to provide a prompt review and approval of complete CEMS Application, CEMS Test Protocol and Report, and CEMS Final Certification when these documents are submitted in a timely manner. Submittal of incomplete documentation for review, and on-site scheduling problems will still delay the review process – expedited, or not. Expedited or "fast track" CEMS review will not provide relief from meeting mandated Permitting and Compliance deadlines, nor will it directly affect issuance of Permit-to Operate.
	I am requesting an expedited CEMS review (Please explain briefly the time constraints or reasons for expedited request, to aid in our assessment of your request):

17. CONFIDENTIALITY Do you regard any of				lential?	
YES NO	- If yes, please	e specify below	v (use additional pag	ges, if necessar	y:
By signing below, I certify the	at all of the information	in this CEMS A	pplication is accurate to	the best of my k	nowledge, and
that I have read the Non-REC that I concur with them.					
S	IGNATURE OF C	COMPANY I	REPRESENTATIV	Æ	
SIGNATURE:			DATE	:	
SIGNATURE.			DATE	•	
(Name)		(Title)	(PHONE)		(DATE)
NOTE: The CEMS C separate projects. Do no		•	mit-to-Construct pro		-
to Permit Processing. completed CEMS Applic	This will only lea				
South Coast Air Quality M 21865 Copley Drive	ANAGEMENT DISTRICT	C/O:	Mr. Rudy Eden, Mana Source Test Engineering		
Diamond Bar, CA 91765-4182	2		Monitoring & Analysi		
A 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	6 : 1 ::1 1.6	SELECT A 11 41	(D. C. D D	1 201/:\/5\ 1	1 4

A basic or initial application fee is due with each CEMS Application (Reference: District Rule 301(i)(5), please complete attached Form ST-400 "RECLAIM & Non-RECLAIM CEMS Plan, Application Fee Processing Form"). A copy of this application is also available on disk, formatted for MS WORD XP or ADOBE ACROBAT. To obtain this form, please check the AQMD Website at www.aqmd.gov, or contact us at (909) 396-3479 (e-mail: pberes@aqmd.gov).

APPENDIX A

SIMPLIFIED PROCESS FLOW DIAGRAM (Reference Section 3)

Show simple flow/block diagram with basic and control equipment including the exhaust stack where the CEMS will be mounted. Be sure to include by-pass ducts, emergency venting stacks, blanked-off stacks, recirculated flows and influent or effluent flow to or from related processes.

APPENDIX B

SIMPLIFIED STACK DIAGRAM (Reference Section 4)

Show the CEMS sampling probe and reference sample port locations (top/cross-section and side views) in the exhaust stack with respect to the upstream and downstream flow disturbances (fans, dampers, transitions, change in stack cross-sectional areas, etc.). Indicate distances and dimensions for the above information. **ACEMS applicants** must show dimensionally, the location of all parametric sensors or monitors with respect to the process equipment, influent and exhaust flows, and reference method sampling locations.

APPENDIX C

SIMPLIFIED CEMS DIAGRAM (Reference Section 5)

Show a flow diagram indicating the routing of sample and calibration gases through the sample acquisition, transport, and conditioning units. This diagram shall include the components of the CEMS (probe, filter, heat traced line, $\mathrm{NO_x}$ converter, conditioning system, sample pumps, flow meters, analyzers, recorders, calibration systems, connecting lines, valves, flow and pressure regulators.) including by-pass vents. Indicate temperature, pressure, and moisture at key points.

10 ACEMS Applicants: Complete APPENDIX G Instead

SIMPLIFIED MULTI-POINT PROBE DIAGRAM (Reference Section 5)

Show a dimensional drawing of the proposed multiple-point probe indicating hole bore, hole spacing with respect to inside stack wall, port flange offset, and center-of-stack. Also include sample routing diagram showing audit port (required), vacuum or differential pressure gage (required), flowmeter/rotometer (required), high-volume pump, heated instrument box (if applicable), and connective tubing/valves. Remember, the multiple-point probe must be successfully bench tested according to AQMD Source Testing *Form 511*: "Multi-Point Probe Acceptance and Quality Assurance Standards, for Use in Conjunction with EPA/EMTIC Guidance Document (GD)-031" before it may be installed on the stack or duct.

Total Points:	(No. Probes:	Pts/Probe:	Bore:)
Pump Specs ¹¹ : Make/Mdl:		Flowrate:	
Sample Audit Port (required	d):	Yes	☐ No
Flow meter ¹² (required):	Rotometer	Other Type:	
Vacuum/differential pressu	re gage ¹² (<i>required</i>):	☐ Vacuum	☐ Diff Press
Probe Blowback capability	(recommended):	Yes	☐ No

_

¹¹ Pump flowrate must be included and be accurate because the probe assembly will be bench-tested and pre-certified at that flowrate. Use of a lower flow pump when the probe is installed on the stack will invalidate the pre-certification.

¹² The probe assembly will be bench-tested exactly as it would be configured on the stack (except for the pump as long as a similar one is

¹² The probe assembly will be bench-tested exactly as it would be configured on the stack (except for the pump as long as a similar one is used) with the vacuum/ Δp and flow devices attached. Vacuum/ Δp and flow measurements are a part of the required parameters to be recorded and documented for pre-certification, and they will be used for on-going QA demonstration.

APPENDIX D

DETERMINATION OF REQUIRED MONITORING PARAMETERS

(Reference Section 6)

Detail, step by step, how the parameters checked in *Section 6* will be applied to the final monitoring requirement by use of equations, assumptions, and calculations. (Be sure to detail how corrections will be made to dry, standard conditions, or conditions imposed by rules or permits). **ACEMS applicants** must include a model of the parametric monitoring system describing the relationship of each monitoring parameter, it's operating range, and redundancy; the operational limit of the process monitored; and equations, algorithms, factors, and coefficients for determining the final monitoring requirement. An electronic copy of the parametric model may also be submitted.

APPENDIX E

BRIEF DESCRIPTION OF COMPUTER PROGRAMMING LOGIC

(Reference Section 7)

Briefly describe how the parameters you described in *Section 6* will be programmed into the data reduction and recording units. Use block diagrams, or a copy of recorded data if needed, to show the location in the program where constants, variables and other parameters are entered. Also include the frequency that each monitoring parameter is polled by the DAS/PLC.

CEMS Designation:

DESCRIPTION OF SOX SOURCE EQUIPMENT SERVED BY A FUEL SULFUR MONITORING SYSTEM (FSMS)

(Reference Sections 2 and 5b.)

Supply the required information. Attach additional copies if required. If the piece of equipment is also a RECLAIM NOx Major Source, be sure to complete a separate CEMS application.

CEMS Description	n:_							
Indicate the type of	of FSMS:		☐ Total Sulfur Mor	nitor 🗌	SOx CEMS			
Equipment Information			Fuel Meter Information					
Equipment	Device I.D., Application, Permit No.	NOx (LGE or MAJ) ¹³	Make & Model	Principle (orifice,etc.)	Proposed Range			

¹³ Applicable to RECLAIM sources only.

(ACEMS Applicants Only)

SUPPLEMENTAL INFORMATION FOR "ACEMS"

(Reference Sections 2 and 5)

ACEMS INFORMATION	This appendix supplement	ts Section 2, and re	eplaces Sections 5	.a. and 5.b.	If you require	more space	for completion	, make
additional copies of this section	on and attach information.	Please attach manu	facturer's specificat	tion sheets in	n <i>Attachment 2</i>			

dditional copies of this section and attach information. Please attach manufacturer's specification sheets in <i>Attachment 2</i>									
1. OPERATIONAL LIMIT OF BASIC EQUIPMENT (as described in <i>Section</i> ACEMS (Note: Following Final Certi	n 2), which the ACEMS p	arametric model wi	ll incorporate, and for wh	nich valid data will be prod	duced by tl	he			
A. LOWER OPERATIONAL LIMIT:		(units) B. Ul	PPER OPERATIONAL LIM	ШТ:		(units)			
2. PARAMETRIC MONITORING IN	FORMATION (serial nu	mbers shall be submitte	d when installation is complet	ed)					
Monitoring Parameter (be specific: manifold vacuum, stack temperature, etc.)	Type Sensor (e.g., thermal anemometer)	Make	Model	Monitoring Range (include units)		itoring rarchy Secondary			

PARAMETRIC MONITORING INFORMATION (CONT'D)

Monitoring Parameter (be specific: manifold vacuum, stack temperature, etc.)	Type Sensor (e.g., thermal anemometer)	Make	Model	Monitoring Range (include units)	Monitoring Hierarchy Primary Secondary	

ATTACHMENT 1

DISTRICT PERMITS AND CORRESPONDENCE

(Reference Sections 2 and 8)

Please attach the following information related to the basic and control equipment to be monitored, to this sheet, and label them as "<u>Attachment 1</u>":

- Applicable permits
- Other pertinent District correspondence

ATTACHMENT 2

MANUFACTURER'S AND/OR VENDOR'S SPECIFICATIONS

(Reference Section 9)

Please attach the following information related to the CEMS (analyzers, components, monitors, data acquisition and recording systems, program logic controllers, etc.), to this sheet, and label them as "Attachment 2":

- Manufacturer's and/or vendor's technical specification sheets
- Other pertinent CEMS information

QUALITY ASSURANCE PLAN (QAP)

(Reference Section 10)

Please attach the following information related to the CEMS QA/QC, and label it as "Attachment 3":

- Copy of <u>complete</u> Quality Assurance Plan (QAP) for this CEMS, or reference to Facility-wide CEMS QAP with specific QA/QC section for this CEMS attached
- If copy of QAP is unfinished/incomplete, provide brief description or outline of QAP

NOTE TO ALL APPLICANTS: The complete QAP must be submitted, and approved before CEMS "Final Certification can be granted.

ATTACHED FORMS

The following forms should be attached:

- <u>FORM ST-300</u>, "<u>CEMS Vendors List"</u> A representative list (not a complete list) of possible CEMS vendors.
- FORM ST-400, "CEMS Fee Sheet"

Please complete the requested information, determine the basic fee charged for the CEMS Certification, Modification, or Change-of-Ownership at your facility; and attach to this submittal along with a check for the required amount.

If either of these forms are missing, you may obtain them at:

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT 21865 Copley Drive Diamond Bar, CA 91765-4182

Source Test Engineering Branch, Monitoring & Analysis Division

(909) 396-3479

RECLAIM & NON-RECLAIM CEMS PLAN, APPLICATION FEE PROCESSING FORM ST-400/1011¹ South Coast Air Quality Management District (Fees are applicable FY 10-11)

1. COMPANY INFO	JKMATION	PLEASE COP	MPLETEIR	E UNSHAL	<u>JED </u> AKEAS O	F IHIS FURI	M (FOR INSTRUCTIONS,	, SEE KE VE	RSE SIDE)
LEGAL NAME OF APP	LICANT:								
BUSINESS MAILING A	ADDRESS:								
2. FACILITY INFORMATION (ONE FACILITY ID PER FORM. SEE REVERSE SIDE FOR MORE INFORMATION)									
FACILITY NAME: FACILITY ID NO:									
							<u>L</u>		
EQUIPMENT/FACILITY	LOCATION: (II	F SAME AS MAIL	LING ADDRF	ESS, ENTE	R "SAME")				
					=		2		
CONTACT PERSON:				CONTA	CT TITLE:		CONTAC	T TELEPH	ONE NO:
3. CEMS PROJEC	יתויג	OTEMIZE I		TIAI DIF	COE OE EOLIJIP	MADNIT & AP	PPLICABLE BASIC PROCE	LOCINIC EE	
INFORMATION		,					PLICABLE BASIC PROCE . USE ADDITIONAL SHEE		
BASIC EQUIPM)MD ID		101101	FEE INFORMA	-	UIKLD)
				_					
(EQUIPMENT MONITOR APPLICA	RED BY CEMS – FR ATION OR PERMIT)		DEVICE ID) (A	/N)	CEMS P	PROJECT DESCRIPTION ²	BA	SIC FEE
				()				
				()				
				()				
				<u> </u>)				
				()				
			†)				
			†)				
	-)			<u> </u>	
			†)				
			<u> </u>)				
					<i>)</i>	Тота	L FEES INCLUDED:		
						IUIA	L FEES INCLUDED .		
SIGNATURE		(IF COM	PLETED BY	COMPAN	Y REPRESENT	ΓΑΤΙVE)			
COMPLETED BY:									
		SPONSIBLE MEMBER	R OF <u>Organiz</u>					Date)	
TYPE OR PRINT NAM	E OF SIGNER:			TITLE (OF SIGNER:		TELEPHON	E No:	
							()		
SCAQMD USE ON	NLY								
SENIOR ENGR:		DIV/BRANCH		A	ASSIGN S/T E	NGR:	(PHONE)	(DAT	E STAMP)
MIKE CECC	ONI	M&AD	D / STE						
TRXN TYPE:	COMMENT:			CHECK 1	No.:		AMOUNT:		
CODE 35	CEMS EVAI	LUATION					\$		

INSTRUCTIONS FOR COMPLETION OF FEE PROCESSING FORM

Complete all of the information requested in <u>Sections 1 and 2, Company and Facility Information</u>. Be sure to include the Facility I.D. No. (from Facility Permit to Operate). If your facility has "major" equipment at more than one location and/or listed under more than one Facility I.D. No., complete one of these forms <u>for each Facility I.D. No.</u>, listing the applicable equipment information for each Facility I.D.-based location.

Refer to the TABLE below when completing <u>Section 3</u>, <u>CEMS Equipment Information</u>. The <u>Basic or Minimum Fee</u> below is the appropriate filing fee for each <u>Project</u> on this form (NOTE: Expedited projects must have AQMD approval before filing). It is an initial accounting, and you may be billed at the completion of the project for additional expenses if any CEMS Project has more components, or utilizes more evaluation time than allocated by that basic fee. Be sure to include the equipment Device I.D., Application or Permit No. (where applicable) from the Facility Permit to Operate. You may include more than one type of fee on a single form, as long as they are clearly marked as to <u>Project and Equipment</u>. Use additional sheets to list equipment, if needed, and total results.

District Rule 301 and 306 Applicable CEMS Processing Fees (Amended May 7, 2010) (Fees Effective for all CEMS submittals beginning July 1, 2010)

District	CEMS Project	Evaluation Fee				
Rule	Description	Basic or	Minimum	Maximum		
	_	Normal	Expedited ¹	Normal	Expedited ¹	
301(j)(5)(A) TABLE IIC, and 301(v)(3)	<u>CEMS Initial Certification</u> or <u>CEMS Modification with</u> <u>Additional Components</u> , according to the following schedule ² :					
	a. 1-2 components, any combination pollutant, diluent, flow:	\$ 3,288.81	\$ 3,288.81	\$ 5,888.47	\$ 10,077.71	
	b. 3-4 components, any combination pollutant, diluent, flow:	\$ 3,956.16	\$ 3,956.16	\$ 10,836.05	\$ 18,665.83	
	c. Each additional component, beyond 4 components, add to "b." above:	+ \$ 0.00	+ \$ 0.00	+ \$ 2,676.71	+ \$ 4,065.11	
	d. <u>Time-Shared CEMS</u> (add to applicable CEMS fee determined above):	+ \$ 0.00	+ \$ 0.00	+ \$ 2,676.71	+ \$ 4,065.11	
301(j)(5)(A) TABLE IIC, and 301(v)(3)	ACEMS Initial Certification (excluding modifications)	\$ 3,288.813	\$ 3,288.81	\$ 10,836.05	\$ 18,665.83	
301(j)(5)(B)(C) (D), and 301(v)(3)	<u>CEMS Modification</u> (excluding additional components) or CEMS monitored equipment, CEMS Periodic Assessment Evaluation	\$ 730.60 ⁴	\$ 730.60	\$ 4,567.83	\$ 7,268.39	
301(j)(5)(E)	<u>CEMS Change of Ownership</u> to facility document files according to the following schedule:					
	a. First CEMS	\$ 217.80				
	b. Each additional CEMS	+ \$ 43.44				

Please return this form (signed and dated), along with the appropriate CEMS Application, Plan, Protocol, Report, Modification, or Change-of-Ownership requiring evaluation; and a check for the total fees. (You may include a single check for the total amount of all submitted fee processing forms):

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT Monitoring & Analysis Division, Source Test Engineering Branch 21865 Copley Drive Diamond Bar, CA 91765-4182

If you require help, or more forms, please contact your assigned CEMS representative, or phone (909) 396-3479.

¹ Requests for expedited evaluations must be approved by AQMD staff before filing, since expedited review is contingent upon availability of qualified staff over and above regular review scheduling. Expedited reviews shall be billed at the hourly premium of \$ 71.02 / hr in addition to normal hourly fees shown below, and as reflected in the expedited "Basic or Minimum Fee", payable at time of filing, and the "Maximum Fee".

² Covers up to 40 hours of evaluation time for the first two components, an additional 20 hours for the first four components, and an additional 12 hours per component beyond four. Excess time will be billed at the hourly rate of \$ 136.92 / hr, up to the maximum allowable fee.

³ Covers up to 40 hours of evaluation time. Excess time will be billed at the hourly rate of \$ 136.92 / hr, up to the maximum allowable fee.

⁴ Covers up to 10 hours of evaluation time. Excess time will be billed at the hourly rate of \$ 136.92 / hr, up to the maximum allowable fee.